## Hydraulic control device.

Patent number:

EP0170815

Publication date:

1986-02-12

Inventor:

**OLBRICH GOTTFRIED DIPL-ING** 

Applicant:

**BOSCH GMBH ROBERT (DE)** 

Classification:

- International:

F15B11/05

- european: Application numbe F15B11/16B6; F15B13/04C2

Application number: EP19850106904 19850604

Priority number(s): DE19843425303 19840710

Also publishe

DE342 EP017

Cited docume

US408 DE262 FR229

US393 US421 more >

## Abstract of EP0170815

1. Hydraulic control device (10) having at least one directional valve (15) which is suitable for controlling an actuator (48) and whose control element (58), in a neutral position (II), shuts off at least one line (46, 51) leading to the actuator (48) and, in two operating positions (1 and II), connects it alternately to a supply line (14) or a return line (17) having a pressure compensator (18) for the direct return to the return line (17) of the pressure medium, supplied form a pressure medium source (11) into the supply line (14) and not required by the actuator (48), having a branch line (22) associated with the pressure compensator (18), into which branch line (22) is connected at least one throttle positions (25) and which leads to a spring (19) loaded control spool (95) of the pressure compensator (18), having a selector valve (32) which is connected, via its medium port (41), a first control line (31) and the branch line (22), to the supply line (14), the first seating port (42) of which selector valve (32) being connected to the return line (17) and its second seating port (43) being connected to the directional valve (15) via at least one line (44, 53) used for accepting the load pressure at the actuator (48), characterized in that a switching valve (24), having a 2/2 function and being hydraulically controlled by the pressure present in the first control line (31), and the at least one second throttle position (26) are located between the control line (31) and the branch line (22), and that the pressure present between the two throttle position (25, 26) is effective at the pressure compensator (18).

